

TECHNICAL SPECIFICATIONS

2026 KTM 1390 SUPER DUKE R EVO

ENGINE

Design **2-CYLINDER, 4-STROKE, V 75°**

Displacement **1350 CM³**

Power **190 PS**

Torque **145 NM**

Transmission **6-SPEED**

CO₂ emissions **139 G/KM**

Cooling **LIQUID COOLED WITH WATER/OIL HEAT EXCHANGER**

Engine cylinder **TWIN CYLINDER**

EMS **KEIHIN EMS WITH RBW AND CRUISE CONTROL, DOUBLE IGNITION**

Engine oil **MOTOREX, SAE 10W-50**

Engine stroke **4-STROKE**

Silencer **STAINLESS STEEL PRIMARY AND SECONDARY SILENCER WITH TWO CATALYTIC CONVERTERS**

CHASSIS

Front brake disc diameter	320 MM
Rear brake disc diameter	240 MM
Front brake	2 X BREMBO STYLEMA MONOBLOC FOUR PISTON, RADIALY MOUNTED CALIPER
Rear brake	BREMBO TWIN-PISTON FIXED CALLIPER, BRAKE DISC
Chain	525 X-RING
Frame design	CHROMIUM-MOLYBDENUM-STEEL TRELIS FRAME, POWDER COATED
Steering head angle	65.3 °
Rear subframe design	CAST ALUMINIUM / COMPOSITE
Trail	101 MM
Wheelbase	1491 MM

SUSPENSION

Front suspension	WP APEX-USD Ø 48 MM, SEMI-ACTIVE (GEN 3)
Rear suspension	WP APEX-LINKAGE SHOCK, SEMI-ACTIVE (GEN 3)
Suspension travel (front)	125 MM
Suspension travel (rear)	140 MM
Rear suspension setting	SEMI-ACTIVE, ELECTRONIC PRELOAD

DIMENSIONS

Seat height	834 MM
-------------	---------------

Wheelbase	1491 ± 15 MM
-----------	---------------------

Tank capacity (approx.)	17.5 L
-------------------------	---------------

Ground clearance	149 MM
------------------	---------------

Weight (without fuel)	200 KG
-----------------------	---------------

Weight fully fueled	212 KG
---------------------	---------------

Wheelbase tolerance	15 MM
---------------------	--------------

Front wheel diameter	17 "
----------------------	-------------

Rear wheel diameter	17 "
---------------------	-------------

Front wheel width	3.50 "
-------------------	---------------

Rear wheel width	6 "
------------------	------------

Wheels	3.50 X 17"; 6 X 17"
--------	----------------------------

Wheels	CAST ALUMINIUM WHEELS
--------	------------------------------