

TECHNICAL SPECIFICATIONS

2026 KTM 690 ENDURO R

ENGINE

Design	1-CYLINDER, 4-STROKE ENGINE
Displacement	692.7 CM ³
Power	79 PS
Torque	73 NM
Transmission	6-SPEED
CO ₂ emissions	99 G/KM
Cooling	LIQUID COOLED
Engine cylinder	SINGLE CYLINDER
EMS	KEIHIN EMS WITH RBW, TWIN IGNITION
Engine oil	MOTOREX POWER SYNTH SAE 10W-50
Engine stroke	4-STROKE
Silencer	STAINLESS STEEL PRIMARY AND SECONDARY SILENCER

CHASSIS

Brake disc diameters (front/rear)	300 / 240 MM
-----------------------------------	---------------------

Front brake disc diameter	300 MM
---------------------------	---------------

Rear brake disc diameter	240 MM
--------------------------	---------------

Front brake	DISC BRAKE
-------------	-------------------

Rear brake	DISC BRAKE
------------	-------------------

Chain	520 X-RING
-------	-------------------

Frame design	CHROMIUM-MOLYBDENUM STEEL TRELIS FRAME, POWDER COATED
--------------	--

Steering head angle	62.3 °
---------------------	---------------

Rear subframe design	SELF-SUPPORTING PLASTIC TANK
----------------------	-------------------------------------

Trail	120 MM
-------	---------------

Wheelbase	1506 MM
-----------	----------------

SUSPENSION

Front suspension

WP XPLOR-USD, Ø 48 MM

Rear suspension

WP XPLOR WITH PRO-LEVER LINKAGE

Suspension travel (front)

265 MM

Suspension travel (rear)

250 MM

Front suspension adjustment

COMPRESSION AND REBOUND ADJUSTABLE

Rear suspension
setting

**COMPRESSION (HIGH AND LOW SPEED), REBOUND AND PRELOAD
ADJUSTMENT**

DIMENSIONS

Seat height	935 MM
Wheelbase	1506 ± 15 MM
Tank capacity (approx.)	13.3 L
Ground clearance	265 MM
Weight (without fuel)	152 KG
Weight fully fueled	162 KG
Wheelbase tolerance	15 MM
Front wheel diameter	21 "
Rear wheel diameter	18 "
Front wheel width	1.85 "
Rear wheel width	2.5 "
Wheels	1.85 X 21"; 2.5 X 18"