

TECHNICAL SPECIFICATIONS

2026 KTM 450 SX-F FACTORY EDITION

ENGINE

Design	1-CYLINDER, 4-STROKE ENGINE
Displacement	449.9 CM ³
Transmission	5-SPEED
Fuel-mixture generation	KEIHIN EFI, THROTTLE BODY 44 MM
EMS	KEIHIN EMS
Clutch primary drive teeth	72
Primary drive	29:72
Engine cylinder	SINGLE CYLINDER
Engine stroke	4-STROKE

CHASSIS

Frame design	CENTRAL DOUBLE-CRADLE-TYPE 25CRM04 STEEL
--------------	---

Front brake	DISC BRAKE
-------------	-------------------

Rear brake	DISC BRAKE
------------	-------------------

Rear subframe design	ALUMINIUM / POLYAMIDE GLASS FIBER
----------------------	--

Chain	520, NON-SEALED
-------	------------------------

SUSPENSION

Front suspension	WP XACT PRO 7548
------------------	-------------------------

Rear suspension	WP XACT PRO 8950
-----------------	-------------------------

Suspension travel (front)	300 MM
---------------------------	---------------

Suspension travel (rear)	300 MM
--------------------------	---------------

Front suspension adjustment	COMPRESSION AND REBOUND ADJUSTABLE
-----------------------------	---

Rear suspension setting	COMPRESSION AND REBOUND ADJUSTABLE, PRELOAD ADJUSTER
-------------------------	---

DIMENSIONS

Seat height	958 MM
-------------	---------------

Ground clearance	343 MM
------------------	---------------

Tank capacity (approx.)	7.2 L
-------------------------	--------------

Weight (without fuel)	106.4 KG
-----------------------	-----------------